

STAGEPAS 1K

Outline

Type: Powered subwoofer with a line array speaker

Mixing capability

Mixing channels: 5 (3 mono + 1 ST)

Input channel functions: Hi-Z: CH2/3, 1-knob EQ: CH1-3/ST

Output channel functions: MODE (SPEECH - MUSIC - CLUB)

I/O

Eingänge: 3 mono mic/line + 1 stereo line/2 mono line

Ausgänge: 1 Link out, 1 Monitor out

Bluetooth: Bluetooth Ver.5.0, A2DP (SBC, AAC)

Control and others: Reverb foot switch, STAGEPAS Editor (iOS/Android app)

On-board processors

DSP: SPX digital reverb (4 program, parameter control)

General specifications

Speaker type: Powered subwoofer: Bass-reflex type, Line array speaker: Enclosed

Frequency range (-10dB): 37 Hz - 20 kHz

Nominal coverage: H: 170° V: 30°

Components: LF: Powered subwoofer: 12" (30 cm) Cone

HF: Line array speaker: 1.5" (3.8 cm) Cone x 10

Power rating: Dynamic: 1000W (Powered subwoofer: 810W, Line array speaker : 190W)

Maximum output level (1m; on axis): 119 dB SPL

Power requirements: Depending on area of purchase: 100V 50Hz/60Hz, 110V/120V 60Hz, 220V-240V 50Hz/60Hz

Power consumption: 25 W (Idle), 85 W (1/8 power)

Accessories: Power cord x 1, Cover x 1

Options Yamaha DL-SP1K (Dedicated dolly), FC5 (foot switch) for reverb ON/OFF

Others: Handle: 1 x Powered subwoofer

Abmessungen (B x H x T): System: 334 x 2,000 x 418 mm (maximum), Line array speaker: 67 x 582 x 86 mm, Powered subwoofer: 334 x 550 x 418 mm, Spacer: 67 x 555 x 86 mm (each)

Gewicht System: 23.0kg (maximum), Line array speaker: 1.8kg, Powered subwoofer: 20.0kg, Spacer: 0.6kg (each)